

TPM Part / No.	26D-1A□1N0	53D-1A□0N3-60	57W-1A□1N0-01	57W-2A□1N0	
SANYU Part / No.					
外觀形狀 Appearance					
尺寸 Size (L×W×H) mm	20.3 x 5.0 x 9.5	30.0 x 13.0 x 14.0	22.5 x 10.7 x 8.1	22.5 x 10.7 x 8.1	
回路接續圖 Figure.(TOP VIEW)					
電氣規格	Contact Form	1 Form A	1 Form A	1 Form A	2 Form A
	Coil Rating Voltage	5 V / 330Ω 12 V / 1800Ω	5 V / 400Ω 12 V / 2250Ω	5 V / 60Ω 12 V / 300Ω 24 V / 1200Ω	5 V / 60Ω 12 V / 300Ω 24 V / 1200Ω
	Contact Rating	10 W	100 W	50 W	50 W
	Contact Current	0.5 Amp	1.0 Amp	1.0 Amp	1.0 Amp
	Carry Current	1.0 Amp	2.8 Amp	5.2 Amp	5.2 Amp
	Switching Voltage	100 VDC	1000 VDC	1000 VDC	1000 VDC
	Contact Voltage	200 VDC	2000 VDC	1000 VDC	1000 VDC
	Contact Resistance	150 mΩ	150 mΩ	50 mΩ	50 mΩ
	Insulation Resistance	10 ¹⁰ Ω min.	10 ¹³ Ω min.	10 ¹⁰ Ω min.	10 ¹⁰ Ω min.
	Operate Time	1.0 mS	1.5 mS	2.5 mS	2.5 mS
	Release Time	1.0 mS	1.0 mS	2.0 mS	2.0 mS
	Operating temperature				
Reflow temperature					
電氣壽命 (代表例) Electrical Life	DC.1.0V,10mA 1000×10 ⁶ (R負荷)	DC.1.0V,10mA 100×10 ⁶ (R負荷)	DC.1.0V,10mA 1000×10 ⁶ (R負荷)	DC.1.0V,10mA 1000×10 ⁶ (R負荷)	
High-frequency response					
外觀尺寸 DIMENSION					
TPM Part Ordering Code : □ = 1 (5VDC); 2 (12VDC); 3 (24VDC); 5 (3.3VDC)					
SANYU Part Ordering Code: ○○ = 03 (3.3VDC); 05 (5VDC); 12 (12VDC); 24 (24VDC)					

TPM Part / No.	58D-3A□1N0-04	92D-1A□1N0	92D-2A□1N0	92D-3A□1N0	
SANYU Part / No.					
外觀形狀 Appearance					
尺寸 Size (L×W×H) mm	30.0 x 16.0 x 13.5	29.0 x 11.8 x 16.0	29.0 x 14.5 x 16.0	29.0 x 17.5 x 16.0	
回路接續圖 Figure.(TOP VIEW)					
電氣規格	Contact Form	3 Form A	1 Form A	2 Form A	3 Form A
	Coil Rating Voltage	5 V / 350Ω 12 V / 1500Ω 24 V / 5000Ω	5 V / 600Ω 12 V / 2400Ω 24 V / 9000Ω	5 V / 500Ω 12 V / 2500Ω 24 V / 10000Ω	5 V / 250Ω 12 V / 1500Ω 24 V / 5000Ω
	Contact Rating	50 W	10 W	10 W	10 W
	Contact Current	0.5 Amp	0.5 Amp	0.5 Amp	0.5 Amp
	Carry Current	2.8 Amp	1.0 Amp	1.0 Amp	1.0 Amp
	Switching Voltage	350 VDC	100 VDC	100 VDC	100 VDC
	Contact Voltage	400 VDC	200 VDC	200 VDC	200 VDC
	Contact Resistance	200 mΩ	200 mΩ	200 mΩ	200 mΩ
	Insulation Resistance	10 ¹⁰ Ω min.	10 ¹⁰ Ω min.	10 ¹⁰ Ω min.	10 ¹⁰ Ω min.
	Operate Time	1.5 mS	1.0 mS	1.0 mS	1.0 mS
	Release Time	1.0 mS	1.0 mS	1.0 mS	1.0 mS
	Operating temperature				
	Reflow temperature				
電氣壽命 (代表例) Electrical Life	DC.1.0V,10mA 1000×10⁶ (R負荷)	DC.1.0V,10mA 1000×10⁶ (R負荷)	DC.1.0V,10mA 1000×10⁶ (R負荷)	DC.1.0V,10mA 1000×10⁶ (R負荷)	
High-frequency response					
外觀尺寸 DIMENSION					
TPM Part Ordering Code : □ = 1 (5VDC); 2 (12VDC); 3 (24VDC); 5 (3.3VDC)					
SANYU Part Ordering Code: ○○ = 03 (3.3VDC); 05 (5VDC); 12 (12VDC); 24 (24VDC)					

TPM Part / No.	92D-1C□1N0	92D-2C□1N0	54D-2E21N2	53D-4A□1N0	
SANYU Part / No.					
外觀形狀 Appearance					
尺寸 Size (L×W×H) mm	29.0 x 11.8 x 16.0	29.0 x 14.5 x 16.0	20.3 x 10.1 x 11.0	30.4 x 17.7 x 13.0	
回路接續圖 Figure.(TOP VIEW)					
電氣規格	Contact Form	1 Form C	2 Form C	2 Form C (A+B)	4 Form A
	Coil Rating Voltage	5 V / 300Ω 12 V / 1600Ω 24 V / 4500Ω	5 V / 250Ω 12 V / 1200Ω 24 V / 4800Ω	12 V / 500Ω	5 V / 200Ω 12 V / 1100Ω 24 V / 3700Ω
	Contact Rating	3 W	3 W	10 W	10 W
	Contact Current	0.25 Amp	0.25 Amp	0.5 Amp	0.5 Amp
	Carry Current	0.5 Amp	0.5 Amp	1.0 Amp	1.0 Amp
	Switching Voltage	100 VDC	100 VDC	100 VDC	100 VDC
	Contact Voltage	200 VDC	200 VDC	200 VDC	200 VDC
	Contact Resistance	200 mΩ	200 mΩ	150 mΩ	150 mΩ
	Insulation Resistance	10 ¹⁰ Ω min.	10 ¹⁰ Ω min.	10 ¹² Ω min.	10 ¹⁰ Ω min.
	Operate Time	2.0 mS	2.0 mS	1.0 mS	1.0 mS
	Release Time	2.5 mS	2.5 mS	1.0 mS	1.0 mS
	Operating temperature				
Reflow temperature					
電氣壽命 (代表例) Electrical Life	DC.1.0V,10mA 50×10 ⁶ (R負荷)	DC.1.0V,10mA 50×10 ⁶ (R負荷)	DC.1.0V,10mA 1000×10 ⁶ (R負荷)	DC.1.0V,10mA 1000×10 ⁶ (R負荷)	
High-frequency response					
外觀尺寸 DIMENSION					
	<p>TPM Part Ordering Code : □ = 1 (5VDC); 2 (12VDC); 3 (24VDC); 5 (3.3VDC)</p> <p>SANYU Part Ordering Code: ○○ = 03 (3.3VDC); 05 (5VDC); 12 (12VDC); 24 (24VDC)</p>				