



# YOUR 1st PARTNER IC-HI

Challenge for density ,  
Challenge for performance

SANYU/TPM surface mount reed relay provides various packages style and features from de-standard to application specified.



Vol. 2022.08

## ◆ 本期焦點



# SEMICON® TAIWAN

國際半導體展

展覽

2022年9月14-16日  
台北南港展覽館一館

論壇

2022年9月13-16日

登錄觀展

同期舉辦

SMART MANUFACTURING 2022 TAIWAN



大交通 Smart Mobility 大未來

智慧製造 Smart Manufacturing

SMC

FLEX



宜技科技有限公司  
IC-HI TECHNOLOGY CO.,LTD.

TEL : 02-2222-9677 / FAX : 02-2222-9833  
Mail : sales@ichitech.com.tw



## ◆ 特別介紹



### 1H-1T13G 微型SMD繼電器 · 持續量產銷售

- 1 Form C ( 1A+1B )
- 12.7 x 5.08 x 7.9 mm
- Switching Voltage : 100V
- Contact Rating 10W
- **Reflow 260°C at 60 sec**
- **Replace : 9852-05-00**



### HV311G4 (A) 業界40v耐壓 · 最高耐電流4.5A

- SMD / DIP / 1 Form A
- Switch Load : **4500mA** & 40VAC or DC ~ max
- Low ON-Resistance : 0.033Ω / Typ.
- Input / Output isolation 3750Vrms
- **REPLACE : AA28 (F)**



### T92H 電力繼電器 (45A/50A)

- 30/40/50A switching capability with small size
- **Overload capability at 75A (DC coil) / 67A (AC coil)**
- Meets requirements of VDE 8mm spacing, 4kV dielectric coil-to-contact
- PCB mounting and quick connect mounting for selection
- UL approved for 600VAC switching (1.5HP)